




CLASSIC FRAME (S-Series & C-Series) - PAIR ACCESS




Shown with TA-8 Steel Casing as example.



Classic Frame - **PAIR ACCESS**



Jamb Hinge Side



Header

CLASSIC FRAME (S-Series & C-Series) - PAIR ACCESS **RELATED INFORMATION** **SOUND** **FIRE RATING**

FRAME MATERIALS	DOOR SIZE AND WEIGHT	JAMB DEPTH RANGES	RATINGS	RATINGS
Prefinished Steel	<p>Door Thickness: 1 3/8" or 1 3/4"</p> <p>Max. Door Width: 2 x 4' - 0"</p> <p>Max. Door Height: 10' - 0" *</p> <p>Max. Door Weight: 200 Lbs. each</p>	<p>Jamb Depths 1 3/8" x 1 3/8" Doors</p> <p>C-Series (18 gage): 4" to 13" in 1/8" increments. 1 3/4" x 1 3/4" Doors</p> <p>C-Series (18 gage): 4 1/2" to 13" in 1/8" increments</p>	Not Available	Not Available
<p>* Height on custom Jamb Depths is limited to 10' - 1" All widths and heights are inside dimensions - net door or glass opening size.</p>				

ROUGH OPENING DIMENSIONS

WIDTH

For a Pair access door frame, the rough opening width is 1 1/4" larger than the total of the nominal door widths.

Width is total nominal door widths plus astragal between doors (if used)


ROUGH OPENING: Nominal Door widths + 1 1/4"

HEIGHT

For Single access door, the rough opening height is 1 1/4" larger than the nominal door height.

Height is the net inside dimension of the frame

ROUGH OPENING: Door height + 1 1/4"



W = Width of doors + astragal (if used) + 1 1/4"

H = Nominal Height (net inside frame dimension) + 1 1/4"